

Flamingo Hammer Mills

Suitable for:-

Lump Breaking, Granulating, Pulping & Size Reduction of material such as Chemicals – Foods – Fruit & Vegetables – Clay – Resins – Grains. Recycling Bread, biscuits and compacting waste. Swing or Fixed Hammers

Features:-

- Stainless Steel contact parts (Grade 304)
- Quick Interchangeable Screens
- Bottom Discharge for Easy Bagging Off
- Easy Cleaning
- Large Feed Openings with Feed Gate
- Heavy Duty Ball Bearing Rotors
- E-Z Kleen Bearings
- Taper Lock Pulleys (standard)
- Fitted with Work Cover approved Safety Switch
- 415 volt 3 phase (standard)

Options:

- Fixed Blades
- Special Motors and variable speed drives
- Grade 316 Stainless Steel or Mild Steel.
- Special designs made to order Hammers of special materials
- Electrical wiring, E-Stop, plug & contactor can be supplied



C-Series Hammer Mills

Specifications

Model	C7	C12	C18	<u>Heavy Duty A16</u>
Capacity Kg/hr *	500	1000	1500	5000
Chamber Size mm	250 dia x 180	250 dia x 300	500 dia x 450	500 dia x 400
Feed Opening mm	180 x 120	300 x 125	450 x 250	400 x 250
kW (HP)	2.2 (3)	4.0 (5.5)	18.5 (25)	22-37 (30 -50)
Overall – Height mm	900	900	1400	1400
Overall – Length mm	1500	1600	2100	2300
Overall – Width mm	530	660	660	660
Rotor Speed RPM	2800	2800	2800	2800
Weight with Motor kg	90	123	340	490
Price All Stainless				
<u>OPTIONS</u>				
Nominate:				
Screens: Sizes				

*Capacity based on maize through a 4.75 mm screen ** Budget Price only

Free Test Facilities are available in our Lane Cove Warehouse

Hammer Mills available for hire

Flamingo Products

Unit 7, 27 Mars Road, Lane Cove West, NSW 2066, Australia

Telephone: 61 2 94273270

Facsimile: 61 2 94273590

Website: www.fleming.com.au

Email: sales@fleming.com.au

