

Flamingo Clamp-on Mixers



Flamingo Clamp-on Mixers are useful for a wide range of Blending, Dissolving or Dispersing Applications.

The Standard Range of Flamingo Mixers are supplied with universal swivel bracket, coupling, 900mm long stainless steel shaft & stainless steel polished cast propellers, IP 55 motor rating, specifications below.

Generally **High Speed Stirrers** give a high shear action and a relatively low pumping capacity. They are most suited to dissolving solids, aerating liquids and chemical reactions.

Slow Speed Stirrers have a high pumping capacity, but low shear action and are most useful for blending miscible liquids and maintaining solids in suspension. Suitable for high flow applications.

Specifications & Price*

KW	RPM	Shaft Diameter	Propellers Number & Size	Weight	Price	
					240 volt	415 volt
.37	175	7/8"	1 only 250mm dia.	24kgs		
.75	175	7/8"	1 only 300mm dia.	32kgs		
1.5	175	7/8"	1 only 300mm dia.	49kgs		
.37	385	7/8"	1 only 250mm dia.	24kgs		
.75	385	7/8"	1 only 300mm dia.	23kgs		
1.5	385	7/8"	1 only 300mm dia.	49kgs		
.37	900	3/4"	2 only 100mm dia.	21kgs		
.75	900	3/4"	2 only 125mm dia.	25kgs		
1.5	900	7/8"	2 only 150mm dia.	43kgs		
.37	1400	3/4"	2 only 100mm dia.	21kgs		
.75	1400	3/4"	2 only 125mm dia.	23kgs		
1.5	1400	7/8"	2 only 150mm dia.	28kgs		

Options:

- Hazardous Area or Stainless Steel Motor
- Variable Speed Drives.
- Specials Made to Order
- Flanged Motors
- Air Motors
- Supplied with Tanks

Flamingo Products

Unit 7, 27 Mars Road, Lane Cove West, NSW 2066, Australia
 Telephone: 61 2 94273270 Facsimile: 61 2 94273590
 Website: www.fleming.com.au Email: sales@fleming.com.au